

DRAGNET System Software

All DRAGNET nodes were installed by Mike Sipior (ASTRON) with CentOS 7 using cobbler and ansible. The cobbler and ansible settings are available in a git repo on the dragnet headnode at `/var/lib/git/dragnet.git/`

Many system software packages have been installed, settings changed, CentOS updated to 7.2, `/opt` (+ some `/usr/local`) installed (by Alexander), while Vlad and Cees installed all pulsar user tools under `/usr/local` (NFS).

Many packages installed by Alexander on DRAGNET have a `/home/alexander/pkg/PKGNAME-install.txt` with commands close to a shell script used to config/build/install the package on DRAGNET.

Most changes have been tracked and should ideally go into the ansible/cobbler settings git repo. However, it is unlikely going to happen (time is better spent on other tasks), so the rough notes are tracked here in case we ever have to reinstall. (Obviously, up-to-date and completeness guarantees of this list are low, but it goes a long way.)

System Config Changes

On top of git repo with ansible/cobbler settings:

Crontab

casacore measures tables

On host dragnet (the script downloads once, then applies the update on all nodes), run the command every Mon 04:00 AM.

This auto-updates the casacore measures tables with info on observatories, solar bodies, leap seconds, int'l earth rotation (IERS) coefficients, etc.

```
[amesfoort@dragnet ~]$ sudo crontab -u lofarsys -l
0 4 * * 1 /opt/IERS/cron-update-IERS-DRAGNET.sh 2>
/home/lofarsys/lofar/var/log/IERS/cron-update-IERS-DRAGNET.log
```

resourcetool

On any host but dragnet (it has no RADB resources), run the [resourcetool](#) command every 20 mins starting 1 min past the hour.

This auto-updates storage claim end times in the Observatory's RADB. Else, Observatory systems will eventually think our disks are full and scheduling observations becomes impossible. But we manage disk space ourselves. (The tool also has some other useful capabilities.)

```
[amesfoort@any_but_dragnet ~]$ sudo crontab -u lofarsys -l
1,21,41 * * * * source /opt/lofar/lofarinit.sh; LOFARENV=PRODUCTION
/opt/lofar/bin/resourcetool --broker=scu001.control.lofar --end-past-tasks-
storage-claims > /home/lofarsys/lofar/var/log/resourcetool/cron-update-
resourcetool-$(HOSTNAME).log 2>&1
```

/etc

Apply /home/amesfoort/etc/* to /etc/

Other

```
newgrp dragnet
umask 0002
chmod 775 /opt
sudo chgrp dragnet /opt # and set setgid bit
/opt/lofar_versions owned by lofarbuild:dragnet mode 775 (or rely on setgid
bit)
sudo chgrp -R dragnet /usr/local/share/aclocal /usr/local/share/applications
/usr/local/share/info /usr/local/share/man # applications/ subdir needed to
install aoflagger as dragnet under /usr/local/
exit
```

as well as for the /data1 and /data2 dirs (/data on dragproc seemed fine when I looked, but maybe others did that manually) (and find out what the '+' is in ls -al)

Install pkgs:

```
lsof
environment-modules
smartmontools
numactl-devel (deps on numactl-libs)
hwloc
hwloc-devel
binutils-devel
atop
htop
strace
ftp
tcpdump
#libnet-devel # for custom arping to ping by MAC
#libpcap-devel # idem
iperf3
nethogs
erfa-devel
armadillo-devel
python-astropy
python-jinja2 # for the FACTOR imaging pipeline module
```

```
python-daemon
python-matplotlib-qt4
python-psycopg2 mysql-connector-python PyGreSQL # LOFAR mysql, postgresql
DB python interface modules (used for self-tests only?)
python2-mock # for python LOFAR self-tests under SAS/ and elsewhere
qpidd-cpp-server-linearstore (add to qpidd pkgs)
patch
elfutils
deltarpm
NetworkManager-config-routing-rules # for policy based routing using
NetworkManager
libgtkmm-2.4-dev libsigc++-2.0-dev # optional; for AOFlogger's rficonsole
dbus-c++-devel # required for awimager2's near-copy of CASA libsynthesis
openblas-devel # required for sagecal
pyfits # required for rmsynthesis
ds9 # required by ds9
geom # required by Shapely python module, for the FACTOR pipeline
progressbar # for losoto (LOfar SOlutions TOol,
https://github.com/revoltek/losoto)
xorg-x11-server-Xvfb # for LOTAAS pipeline
mercurial
vim-X11
colordiff
ddd

# for slurm (NOTE: -devel pkgs only needed on head node to build RPMs; non-
devel needed on other nodes)
munge
munge-devel
readline-devel
pam-devel
lua-devel
mailx # also for robinhood
man2html
freeipmi-devel
json-c-devel
rrdtool-devel
libibmad-devel
libibumad-devel
perl-Switch # to install created slurm RPMs
perl-DBI # idem

# to create slurm and lustre client RPMs, head node only:
rpm-build
perl-ExtUtils-MakeMaker

# ensure not specifically installed:
libpng12-devel # since we use libpng-devel (implied)

On drg nodes (ib tools)
libmlx4
```

libibverbs-utils

libibverbs

perftest

qperf

libibverbs-devel # on head node is enough

librdmacm-devel # idem

mstflint # idem

Python packages N/A in CentOS package manager; use pip install

python-monetdb # for LOFAR GSM (imaging); on the head node we did: sudo

pip install --target=/usr/local/lib/python2.7/site-packages python-monetdb

xmlrunner # for LOFAR Pipeline tests; on the head node we did: sudo

pip install --target=/usr/local/lib/python2.7/site-packages xmlrunner

/etc/yum/pluginconf.d/fastestmirror.conf

enabled=0

(into ansible)

dragnet node: time is no longer in UTC (fixed; but check ansible)

dragnet node:

sudo systemctl enable nfs-server

sudo systemctl start nfs-server

dragnet node:

dd if=/dev/urandom bs=1 count=1024 >/etc/munge/munge.key (set owner=munge
group=munge mode=400)

other nodes:

copy this file to local /etc/munge/

each host:

sudo systemctl enable munge

sudo systemctl start munge

add slurm system user and group

create slurm RPMs on hostname

install RPMs on all hosts

copy slurm.conf and gres.conf to all hosts # RPM install creates

/etc/slurm/

create /var/spool/slurmd/

dragnet node:

sudo systemctl enable slurmctld slurmd

sudo systemctl start slurmctld slurmd

dragproc:

sudo systemctl enable slurmctld slurmd slurmdbd

sudo systemctl start slurmctld slurmd slurmdbd

drg:

sudo systemctl enable slurmd

```
sudo systemctl start slurmd
```

set GPUs in persistence mode before slurmd starts (on drgXX nodes only): Use my ~amesfoort/nvidia-smi-pm.service copied into /usr/lib/systemd/system/ and then run:

```
sudo systemctl daemon-reload
```

```
sudo systemctl enable nvidia-smi-pm
```

check networking/interface settings in ansible, and in /etc/sysconfig/network-scripts. Use system-config-network tool to edit. ONBOOT=no too often. MTU 9000 for 10G i/f, ib netmask must be /16 (not /13 as it clashes with cep2 routes), etc...

add routes to CEP2 (and others). Use dragnet-node-routes-10g.sh

Set CONNECTED_MODE=Yes See /home/alexander/Downloads/linux-kernel/linux-3.10.85/Documentation/infiniband/ipoib.txt

Why the heck is this route in drg* routing tables??? (Useful for virt 10G/ib netw?): 169.254.0.0/16 dev ib0 scope link metric 1005

Has Mike fixed the (cobbler?) routing issue via portal? Must go via PD-0 (xxx.5 -> .6 or vice versa)

- Add ping test script: also useful to see what hostnames/domainnames should work.

And fix the idiotic domainname crap!!!

```
systemctl enable NetworkManager-dispatcher.service
```

```
systemctl start NetworkManager-dispatcher.service
```

Correct table example drgl6 (except that CEP2 routes and sub-tables can now be removed):

```
[amesfoort@drgl6 network-scripts]$ ip ru
```

```
0: from all lookup local
```

```
1000: from 10.168.145.1 lookup 1
```

```
32766: from all lookup main
```

```
32767: from all lookup default
```

```
[amesfoort@drgl6 ~]$ ip r l t 1
```

```
10.135.252.0/24 via 10.175.255.201 dev ens5 proto static
```

```
10.135.253.0/24 via 10.175.255.202 dev ens5 proto static
```

```
10.135.254.0/24 via 10.175.255.203 dev ens5 proto static
```

```
10.135.255.0/24 via 10.175.255.204 dev ens5 proto static
```

```
[amesfoort@drgl6 network-scripts]$ ip r
```

```
default via 10.151.255.254 dev em1 proto static metric 100
```

```
10.134.224.0/19 dev ib0 proto kernel scope link src 10.134.224.18 metric 150
```

```
10.144.0.0/13 dev em1 proto kernel scope link src 10.149.160.18 metric 100
```

```
10.168.0.0/13 dev ens5 proto kernel scope link src 10.168.145.1 metric 100
```

```
10.176.0.0/13 via 10.175.255.254 dev ens5 proto static
```

cexec (C3 Cluster Command & Control Suite) into ansible, incl /etc/c3.conf symlink to /usr/local/etc/c3.conf

casacore + casacore-python + measures_tables

```
LOFAR build
lofardal build
/mnt (or /net (/net N/A on debian)) automounts
```

lofarbuild jenkins pub key (head node) into ansible (separate task, since it may change)

lofarsys ssh authorized ssh key (?)

LOFAR settings: lofarsys sudo RT, shmем, ptrace, max CPU(+GPU?) clock when observing(?), RLIMIT_MEMLOCK (also for ibverbs), ... (see cbt009:/etc/rc.local.d/)

add LOFAR/trunk/RTCP/Cobalt/OutputProc/etc/sudoers.d/setcap_cobalt to /etc/sudoers.d/ and ensure it's included via /etc/sudoers (it seems Mike changed sudoers on dragnet, but not elsewhere, now equal, but not yet in ansible)

lofarsys is NFS account; fix this (note: fix up ssh login failures, since keys are then no longer accessible)

lofarsys: ensure dirs exist on all nodes (local account):

lofar/var/{run,log}

lofarsys: ~/.ssh/config:

NoHostAuthenticationForLocalhost yes

Host dragnet dragnet.control.lofar dragproc dragproc-10g

dragproc.control.lofar dragproc-10g.online.lofar drg?? drg??control.lofar

drg??-10g drg??-10g.online.lofar drg??-ib drg??-ib.dragnet.infiniband.lofar

StrictHostKeyChecking no

qpid script to create local queues once

CUDA pkgs on *all* nodes after adding NVIDIA 'cuda' repo: (we use the 'elrepo' driver and the 'cuda' cuda pkgs)

cuda-repo-rhel7

Note: the following 2 pkgs + deps will go into /usr/local, while we want them into /opt, so ask Mike which rpm he used instead

cuda-toolkit-7-0 # if still needed

cuda-toolkit-7-5

install pkgs from ~/pkg such as log4cplus, ...

add changed /etc/modulefiles/* to ansible

/etc/security/limits.conf:

set 'nofile' soft limit to 4k (hard was requested to 10k, but meaningless?)

----- Remove on all nodes:

add '--auth no' to allnodes:/usr/lib/systemd/system/qpid.service

```

(only needed on the src side of the g, but since we need to fwd, it's needed
on all our nodes)
ExecStart=/usr/sbin/qpid --config /etc/qpid/qpid.conf --auth no
----- Replace by on all nodes (qpid.service is replaced on pkg update):
Add auth=no in /etc/qpid/qpid.conf
-----
Then run: (maybe there's a systemctl command to do both of this in one go?)
sudo systemctl daemon-reload
sudo systemctl enable qpid
sudo systemctl restart qpid
(& check if systemctl enable qpid (and start qpid) are indeed in ansible)

added routing table entries for drg*, dragproc in ansible

-----
for lustre mount cep4 (drg nodes only (need ib atm), further install by hand
atm (need rpm rebuild from src rpm)). On all drgXX nodes:
# create /etc/modprobe.d/lnet.conf with:
options lnet networks=o2ib(ib0)

# create/adjust /etc/modprobe.d/ko2iblnd.conf with:
#comment out any 'alias' and 'options' lines other than the next (which MUST
match the settings on the Lustre MGS (and thus all other clients as well)):
options ko2iblnd peer_credits=128 peer_credits_hiw=64 credits=2048
concurrent_sends=256 ntx=2048 map_on_demand=32 fmr_pool_size=2048
fmr_flush_trigger=512 fmr_cache=1
# optional:
install ko2iblnd /usr/sbin/ko2iblnd-probe

# create mount point as root:
mkdir -p /cep4data

# append to /etc/fstab
meta01.cep4.infiniband.lofar@o2ib:meta02.cep4.infiniband.lofar@o2ib:/cep4-fs
/cep4data lustre defaults,ro,flock,noauto 0 0

-----

LTA stuff (may turn out unnecessary when we can finally ingest from DRAGNET,
since it'll have to go via lexar nodes)

globus-gass-copy-progs
voms-clients-cpp
#voms-clients-java # not needed

wget
http://repository.egi.eu/sw/production/cas/1/current/repo-files/EGI-trustanc
hors.repo
sudo mv EGI-trustanchors.repo /etc/yum.repos.d/
(currently on dragnet, it's called egi.repo)

```

```
-----
[EGI-trustanchors]
name=EGI-trustanchors
baseurl=http://repository.egi.eu/sw/production/cas/1/current/
pgpkey=http://repository.egi.eu/sw/production/cas/1/GPG-KEY-EUGridPMA-RPM-3
pgpcheck=1
enabled=1
-----

ca-policy-egi-core # from EGI-trustanchors repo

wget
http://www.lofar.org/operations/lib/exe/fetch.php?media=public:srmclient-2.6
.28.tar.gz
wget
http://www.lofar.org/wiki/lib/exe/fetch.php?media=public:lta-url-copy.sh.gz

(already set up SRM module file)

/etc/vomses, $HOME/.voms/vomses, $HOME/.glite/vomses any filename, e.g.
lofar-voms
-----
"lofar" "voms.grid.sara.nl" "30019"
"/O=dutchgrid/O=hosts/OU=sara.nl/CN=voms.grid.sara.nl" "lofar"
-----

/etc/grid-security/vomsdir/lofar/voms.grid.sara.nl.lsc
-----
/O=dutchgrid/O=hosts/OU=sara.nl/CN=voms.grid.sara.nl
/C=NL/O=NIKHEF/CN=NIKHEF medium-security certification auth
-----
```

From:

<https://www.astron.nl/lofarwiki/> - **LOFAR Wiki**

Permanent link:

https://www.astron.nl/lofarwiki/doku.php?id=dragnet:system_software&rev=1499688326

Last update: **2017-07-10 12:05**

