

Advanced ways to find and retrieve data in the LTA

There are some useful ways to find and retrieve your data in the LTA that might not be immediately obvious. This page explains some of the more advanced options you have.

Queries

- You can use colons in numeric queries, to select ranges. This will for example give all observations and pipelines that have a SAS/Observation ID in the range from 432000 to 432190:

Observation Id	432000:432190
Observing or Pipeline Run Date	From 0000-00-00 00:00:00 To 0000-00-00 00:00:00
Project	any
Maximum Number of Rows	

In textual entries, wildcards can be used.

Target Name	3c19*
-------------	-------

- You can put a list of SAS/Observation IDs in the query:

Observation Id	146112,147775,151778
Observing Date	From 0000-00-00 00:00:00 To 0000-00-00 00:00:00

Viewing data

When you are looking at the results of a query you might see something like this:

Number Of Correlated DataProducts
0 / 488

This means that the observation is known in the LTA, it knows what data was produced, the produced data was not archived, but further processing happened on the raw data and the results of some of those pipelines were archived. If you click on the zero, you will see something like this:

#	<input type="checkbox"/>	DataProduct Identifier	SubArray Pointing Identifier	Subband	Stations	Observations	Pipeline	Derived DataProducts
1		7260485	293855	479	show	1		AveragingPipeline
2		7260483	293855	477	show	1		AveragingPipeline
3		7260488	293855	482	show	1	back to observation	AveragingPipeline
4		7260489	293855	483	show	1		AveragingPipeline
5		7260492	293855	486	show	1		AveragingPipeline
6		7260490	293855	484	show	1		AveragingPipeline
7	Can not be downloaded	7260493	293855	487	show	1		AveragingPipeline
8		7260486	293855	480	show	1		AveragingPipeline
9		7260487	293855	481	show	1	To pipeline	AveragingPipeline
10		7260482	293855	476	show	1		AveragingPipeline
11		7260491	293855	485	show	1		AveragingPipeline
12		7260484	293855	478	show	1		AveragingPipeline
13		7260436	293854	430	show	1		AveragingPipeline

This allows you to navigate from a pipeline back to the original observation, or from the observation to any pipelines that have run on the raw data.

Retrieving data

- You can retrieve data on the Observation and Pipeline level, you don't have to select all files individually.

#	<input type="checkbox"/>	Observation Id	Observing Mode	Antenna Set	Instrun Filte
1	<input checked="" type="checkbox"/>	146448	Interferometer	HBA Dual Inner	110-190
2	<input type="checkbox"/>	146447	Interferometer	HBA Dual Inner	110-190
3	<input checked="" type="checkbox"/>	146446	Interferometer	HBA Dual Inner	110-190
4	<input type="checkbox"/>	146445	Interferometer	HBA Dual Inner	110-190
5	<input checked="" type="checkbox"/>	146444	Interferometer	HBA Dual Inner	110-190
6	<input checked="" type="checkbox"/>	146443	Interferometer	HBA Dual Inner	110-190
7	<input type="checkbox"/>	146442	Interferometer	HBA Dual Inner	110-190
8	<input checked="" type="checkbox"/>	146441	Interferometer	HBA Dual Inner	110-190
9	<input checked="" type="checkbox"/>	146456	Interferometer	HBA Dual Inner	110-190
10	<input checked="" type="checkbox"/>	146455	Interferometer	HBA Dual Inner	110-190
11	<input type="checkbox"/>	146454	Interferometer	HBA Dual Inner	110-190
12	<input type="checkbox"/>	146453	Interferometer	HBA Dual Inner	110-190
13	<input type="checkbox"/>	146452	Interferometer	HBA Dual Inner	110-190

- If you have a query with more than 1000 results, you can open the multiple pages each in a separate tab/window.

Observation 1001 to 1100 (showing 100 of total 1156) ▾

edit columns | stage selected

first | previous | ... | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | next | last

r Of SubArray	Start Time	Duration	Nr Stations	Nr Stations
---------------	------------	----------	-------------	-------------

- With the small triangle next to a list, you can fold or unfold the list to get a better overview.

Folded entries

Observation 1 to 100 (showing 100 of total 1156) ▲

Averaging Pipeline 1 to 100 (showing 100 of total 4060) ▲

Calibration Pipeline (total 30) ▲

Imaging Pipeline (total 0) ▲

UnspecifiedProcess 1 to 100 (showing 100 of total 125) ▲

Unfolded entries

Calibration Pipeline (total 30) -

db-view | map-view

#	Process Name	Process Version	Process Identifier	Observation ID	Start Time	Duration (s)	End Time	Strategy Name	Strategy Description	Progressive Integration Step	Time Integration Step	Flag Rate Correlation	Stimulus Database	Sampling	Number Of Instruments	Number Of Correlated DataProducts	Source DataProduct
1	PMB_AveragingPipeline	1.0.0	407000	123456	2010-01-01 00:00:00	0.0	2010-01-01 00:00:00	Programme Pipeline (no device)	Programme Pipeline (no device)	10	0	0	0	0	0	0	data
2	PMB_AveragingPipeline	1.0.0	407001	123457	2010-01-01 00:00:00	0.0	2010-01-01 00:00:00	Programme Pipeline (no device)	Programme Pipeline (no device)	10	0	0	0	0	0	0	data
3	PMB_AveragingPipeline	1.0.0	407002	123458	2010-01-01 00:00:00	0.0	2010-01-01 00:00:00	Programme Pipeline (no device)	Programme Pipeline (no device)	10	0	0	0	0	0	0	data
4	PMB_AveragingPipeline	1.0.0	407003	123459	2010-01-01 00:00:00	0.0	2010-01-01 00:00:00	Programme Pipeline (no device)	Programme Pipeline (no device)	10	0	0	0	0	0	0	data
5	PMB_AveragingPipeline	1.0.0	407004	123460	2010-01-01 00:00:00	0.0	2010-01-01 00:00:00	Programme Pipeline (no device)	Programme Pipeline (no device)	10	0	0	0	0	0	0	data
6	PMB_AveragingPipeline	1.0.0	407005	123461	2010-01-01 00:00:00	0.0	2010-01-01 00:00:00	Programme Pipeline (no device)	Programme Pipeline (no device)	10	0	0	0	0	0	0	data
7	PMB_AveragingPipeline	1.0.0	407006	123462	2010-01-01 00:00:00	0.0	2010-01-01 00:00:00	Programme Pipeline (no device)	Programme Pipeline (no device)	10	0	0	0	0	0	0	data
8	PMB_AveragingPipeline	1.0.0	407007	123463	2010-01-01 00:00:00	0.0	2010-01-01 00:00:00	Programme Pipeline (no device)	Programme Pipeline (no device)	10	0	0	0	0	0	0	data
9	PMB_AveragingPipeline	1.0.0	407008	123464	2010-01-01 00:00:00	0.0	2010-01-01 00:00:00	Programme Pipeline (no device)	Programme Pipeline (no device)	10	0	0	0	0	0	0	data
10	PMB_AveragingPipeline	1.0.0	407009	123465	2010-01-01 00:00:00	0.0	2010-01-01 00:00:00	Programme Pipeline (no device)	Programme Pipeline (no device)	10	0	0	0	0	0	0	data
11	PMB_AveragingPipeline	1.0.0	407010	123466	2010-01-01 00:00:00	0.0	2010-01-01 00:00:00	Programme Pipeline (no device)	Programme Pipeline (no device)	10	0	0	0	0	0	0	data
12	PMB_AveragingPipeline	1.0.0	407011	123467	2010-01-01 00:00:00	0.0	2010-01-01 00:00:00	Programme Pipeline (no device)	Programme Pipeline (no device)	10	0	0	0	0	0	0	data
13	PMB_AveragingPipeline	1.0.0	407012	123468	2010-01-01 00:00:00	0.0	2010-01-01 00:00:00	Programme Pipeline (no device)	Programme Pipeline (no device)	10	0	0	0	0	0	0	data
14	PMB_AveragingPipeline	1.0.0	407013	123469	2010-01-01 00:00:00	0.0	2010-01-01 00:00:00	Programme Pipeline (no device)	Programme Pipeline (no device)	10	0	0	0	0	0	0	data
15	PMB_AveragingPipeline	1.0.0	407014	123470	2010-01-01 00:00:00	0.0	2010-01-01 00:00:00	Programme Pipeline (no device)	Programme Pipeline (no device)	10	0	0	0	0	0	0	data
16	PMB_AveragingPipeline	1.0.0	407015	123471	2010-01-01 00:00:00	0.0	2010-01-01 00:00:00	Programme Pipeline (no device)	Programme Pipeline (no device)	10	0	0	0	0	0	0	data
17	PMB_AveragingPipeline	1.0.0	407016	123472	2010-01-01 00:00:00	0.0	2010-01-01 00:00:00	Programme Pipeline (no device)	Programme Pipeline (no device)	10	0	0	0	0	0	0	data
18	PMB_AveragingPipeline	1.0.0	407017	123473	2010-01-01 00:00:00	0.0	2010-01-01 00:00:00	Programme Pipeline (no device)	Programme Pipeline (no device)	10	0	0	0	0	0	0	data
19	PMB_AveragingPipeline	1.0.0	407018	123474	2010-01-01 00:00:00	0.0	2010-01-01 00:00:00	Programme Pipeline (no device)	Programme Pipeline (no device)	10	0	0	0	0	0	0	data
20	PMB_AveragingPipeline	1.0.0	407019	123475	2010-01-01 00:00:00	0.0	2010-01-01 00:00:00	Programme Pipeline (no device)	Programme Pipeline (no device)	10	0	0	0	0	0	0	data
21	PMB_AveragingPipeline	1.0.0	407020	123476	2010-01-01 00:00:00	0.0	2010-01-01 00:00:00	Programme Pipeline (no device)	Programme Pipeline (no device)	10	0	0	0	0	0	0	data
22	PMB_AveragingPipeline	1.0.0	407021	123477	2010-01-01 00:00:00	0.0	2010-01-01 00:00:00	Programme Pipeline (no device)	Programme Pipeline (no device)	10	0	0	0	0	0	0	data
23	PMB_AveragingPipeline	1.0.0	407022	123478	2010-01-01 00:00:00	0.0	2010-01-01 00:00:00	Programme Pipeline (no device)	Programme Pipeline (no device)	10	0	0	0	0	0	0	data
24	PMB_AveragingPipeline	1.0.0	407023	123479	2010-01-01 00:00:00	0.0	2010-01-01 00:00:00	Programme Pipeline (no device)	Programme Pipeline (no device)	10	0	0	0	0	0	0	data
25	PMB_AveragingPipeline	1.0.0	407024	123480	2010-01-01 00:00:00	0.0	2010-01-01 00:00:00	Programme Pipeline (no device)	Programme Pipeline (no device)	10	0	0	0	0	0	0	data
26	PMB_AveragingPipeline	1.0.0	407025	123481	2010-01-01 00:00:00	0.0	2010-01-01 00:00:00	Programme Pipeline (no device)	Programme Pipeline (no device)	10	0	0	0	0	0	0	data
27	PMB_AveragingPipeline	1.0.0	407026	123482	2010-01-01 00:00:00	0.0	2010-01-01 00:00:00	Programme Pipeline (no device)	Programme Pipeline (no device)	10	0	0	0	0	0	0	data
28	PMB_AveragingPipeline	1.0.0	407027	123483	2010-01-01 00:00:00	0.0	2010-01-01 00:00:00	Programme Pipeline (no device)	Programme Pipeline (no device)	10	0	0	0	0	0	0	data
29	PMB_AveragingPipeline	1.0.0	407028	123484	2010-01-01 00:00:00	0.0	2010-01-01 00:00:00	Programme Pipeline (no device)	Programme Pipeline (no device)	10	0	0	0	0	0	0	data
30	PMB_AveragingPipeline	1.0.0	407029	123485	2010-01-01 00:00:00	0.0	2010-01-01 00:00:00	Programme Pipeline (no device)	Programme Pipeline (no device)	10	0	0	0	0	0	0	data

Imaging Pipeline (total 0) -

db-view | map-view

UnspecifiedProcess 1 to 100 (showing 100 of total 125) -

db-view | map-view

#	Observation ID	Observation Name	Process Description	Start Time	Duration (s)	Number Of Unspecified DataProducts
1	123456	Unspecified process, information generated by target	2010-01-01 00:00:00	0.0	0	
2	123457	Unspecified process, information generated by target	2010-01-01 00:00:00	0.0	0	
3	123458	Unspecified process, information generated by target	2010-01-01 00:00:00	0.0	0	
4	123459	Unspecified process, information generated by target	2010-01-01 00:00:00	0.0	0	
5	123460	Unspecified process, information generated by target	2010-01-01 00:00:00	0.0	0	
6	123461	Unspecified process, information generated by target	2010-01-01 00:00:00	0.0	0	
7	123462	Unspecified process, information generated by target	2010-01-01 00:00:00	0.0	0	
8	123463	Unspecified process, information generated by target	2010-01-01 00:00:00	0.0	0	
9	123464	Unspecified process, information generated by target	2010-01-01 00:00:00	0.0	0	
10	123465	Unspecified process, information generated by target	2010-01-01 00:00:00	0.0	0	
11	123466	Unspecified process, information generated by target	2010-01-01 00:00:00	0.0	0	
12	123467	Unspecified process, information generated by target	2010-01-01 00:00:00	0.0	0	
13	123468	Unspecified process, information generated by target	2010-01-01 00:00:00	0.0	0	
14	123469	Unspecified process, information generated by target	2010-01-01 00:00:00	0.0	0	
15	123470	Unspecified process, information generated by target	2010-01-01 00:00:00	0.0	0	
16	123471	Unspecified process, information generated by target	2010-01-01 00:00:00	0.0	0	
17	123472	Unspecified process, information generated by target	2010-01-01 00:00:00	0.0	0	
18	123473	Unspecified process, information generated by target	2010-01-01 00:00:00	0.0	0	
19	123474	Unspecified process, information generated by target	2010-01-01 00:00:00	0.0	0	
20	123475	Unspecified process, information generated by target	2010-01-01 00:00:00	0.0	0	
21	123476	Unspecified process, information generated by target	2010-01-01 00:00:00	0.0	0	
22	123477	Unspecified process, information generated by target	2010-01-01 00:00:00	0.0	0	
23	123478	Unspecified process, information generated by target	2010-01-01 00:00:00	0.0	0	
24	123479	Unspecified process, information generated by target	2010-01-01 00:00:00	0.0	0	
25	123480	Unspecified process, information generated by target	2010-01-01 00:00:00	0.0	0	
26	123481	Unspecified process, information generated by target	2010-01-01 00:00:00	0.0	0	
27	123482	Unspecified process, information generated by target	2010-01-01 00:00:00	0.0	0	
28	123483	Unspecified process, information generated by target	2010-01-01 00:00:00	0.0	0	
29	123484	Unspecified process, information generated by target	2010-01-01 00:00:00	0.0	0	
30	123485	Unspecified process, information generated by target	2010-01-01 00:00:00	0.0	0	

DBView

There is a server that gives the option to run your own queries on the database

<http://lofar-dbview.target.rug.nl/>

A useful query might be this one, that gives you all files for a certain Obs Id (SAS VIC tree ID).

```
SELECT fo.URI, dp."dataProductType", dp."dataProductIdentifier",
       dp."processIdentifier"
FROM AWOPER."DataProduct+" dp,
       AWOPER.FileObject fo,
       AWOPER."Process+" pr
WHERE dp."processIdentifier" = pr."processIdentifier"
      AND pr."observationId" = '123456'
      AND fo.data_object = dp."object_id"
```

```
AND dp."isValid" > 0
```

In this '123456' should be replaced with the Obs Id of an Observation/Pipeline you're looking for. Pipelines also have an "observationId" == the SAS Id, even though that's a bit confusing. To be able to run this query, you have to go to the link above, login as the right user, select the right project, and then put this query into the "Manual SQL".

Example You can also modify these queries. for example if you want to also know the MD5 checksum, you can run:

```
SELECT fo.URI, fo.hash_md5, dp."dataProductType",
dp."dataProductIdentifier",
dp."processIdentifier"
FROM AWOPER."DataProduct+" dp,
      AWOPER.FileObject fo,
      AWOPER."Process+" pr
WHERE dp."processIdentifier" = pr."processIdentifier"
      AND pr."observationId" = '123456'
      AND fo.data_object = dp."object_id"
      AND dp."isValid" > 0
```

AstroWise Python Interface

There is a Python client library for accessing the LTA. With this library, you can script your own queries. The installation description can be found here: [LTA Client installation](#). Be sure to have the latest version installed. Note that since January 2018 this library uses python3, python2 is no longer supported.

Once you have installed the client, set up your user name and password. These are the same as for MoM. Remember that this is just a different interface to the LTA catalogue: you will need the same credentials as for the web interface.

After installing the LTA client, the file .awe/Environment.cfg will appear in your home directory (if not, then create one). Make sure the file at least contains the following lines:

```
[global]
database_engine      : oracle_11g
database_name        : db.lofar.target.rug.nl

database_user        : <your username>
database_password    : <your password>
```

Finally, your hostname may cause an error, if it does not contain a full domain. In this case, you will need to edit your /etc/hosts file (you will need root/superuser privileges to do so). In that file, you should find a line that looks like this

```
127.0.0.1 localhost
```

Change that line into

```
127.0.0.1 localhost <your_host_name>
```

If you do not know your hostname, just type hostname in a shell and you will get it as an output.

Now, you can use the following script as a test. It may still give you some warnings, but if it prints out a list of pointings, then you are ready to go. You may need to kill the script, because it will print out all the observations in a certain patch of the sky archived in the LTA.

```
# Python3 code
from pprint import pprint
from awlofar.main.aweimports import Observation, Pointing, SubArrayPointing
from common.database.Context import context
result = {}
for project in sorted(context.get_projects()) :
    print("Project %(project)s" % vars())
    ok = context.set_project(project)
    # do your query
    obs_ids = set()
    query = (Pointing.rightAscension > 95) & \
            (Pointing.rightAscension < 105) & \
            (Pointing.declination > 20) & \
            (Pointing.declination < 30)
    print("Total Pointings %d" % len(query))
    for pointing in query :
        print("Pointing found RA %f DEC %f" % (pointing.rightAscension,
        pointing.declination))
        query_subarr = SubArrayPointing.pointing == pointing
        for subarr in query_subarr:
            query_obs = Observation.subArrayPointings.contains(subarr)
            for obs in query_obs :
                obs_ids.add(obs.observationId)
    result[project] = sorted(list(obs_ids))
    print(result[project])

pprint(result)
```

If you get errors and do not manage to view the list of pointings, there may be the need to open some port on the firewall at your institution. Specifically, port 1521 should be open. In case of trouble, get in contact with Science Operations and Support.

Examples

Once you have tested that your connection to the catalogue is working, you are ready to browse the archive and stage the data you need. Here we will list a few examples of python scripts that can be used to access the LTA. All of them will need to import some modules:

```
from datetime import datetime
from awlofar.database.Context import context
from awlofar.main.aweimports import CorrelatedDataProduct, \
```

```
FileObject, \
Observation
from awlofar.toolbox.LtaStager import LtaStager, LtaStagerError
```

The lines above must be added to each of the scripts below for these to work.

This simple script will allow you to find all data within a single project, for example LC2_035. Please change the project name to the code of a project of yours. If you also want to stage the data you found, just set the do_stage variable to True. Be careful with how many files you stage and what size they have: the same limits as for the web interface apply here.

```
# Should the found files be staged ?
do_stage = False
# The project to query, LC2_035 has public data
project = 'LC2_035'
# The class of data to query
cls = CorrelatedDataProduct
# Query for private data of the project, you must be member of the project
private_data = False

# To see private data of this project, you must be member of this project
if private_data :
    context.set_project(project)
    if project != context.get_current_project().name:
        raise Exception("You are not member of project %s" % project)

query_observations = Observation.select_all().project_only(project)
uris = set() # All URIS to stage
for observation in query_observations :
    print("Querying ObservationID %s" % observation.observationId)
    # Instead of querying on the Observations of the DataProduct, all
    # DataProducts could have been queried
    dataproduct_query = cls.observations.contains(observation)
    # isValid = 1 means there should be an associated URI
    dataproduct_query &= cls.isValid == 1
    for dataproduct in dataproduct_query :
        # This DataProduct should have an associated URL
        fileobject = ((FileObject.data_object == dataproduct) &
            (FileObject.isValid > 0)).max('creation_date')
        if fileobject :
            print("URI found %s" % fileobject.URI)
            uris.add(fileobject.URI)
        else :
            print("No URI found for %s with dataProductIdentifier %d" %
                (dataproduct.__class__.__name__, dataproduct.dataProductIdentifier))

print("Total URI's found %d" % len(uris))

if do_stage :
    stager = LtaStager()
    stager.stage_uris(uris)
```

The following script will find subbands 301 and 302 for all targets within two different projects.

Pay attention to the difference between the keys `subband` and `stationSubband`; the former is a sequential number assigned to each subband in an observation, while the latter is linked to the frequency at which the observation was performed. Example: an observation was set up covering the range 30-77.3 MHz with two simultaneous beams using 244 subbands each. In this case, `subband` will range from 0 to 487, while `stationSubband` from 153 to 396. The `stationSubband` information is stored in the observation, but not in the pipeline products (which instead contain the frequency). If you want to search on `stationSubband`, you must perform your search on observations first, then fetch the pipelines linked to those observations. If you use frequency, you can search directly on pipelines.

As a general advise, before performing a search, you need to **understand thoroughly the meaning of the keywords that you are using and where their values are stored**, otherwise you may not find the data you are looking for.

```
do_stage = False
project1 = 'LC2_016'
project2 = 'LC2_012'
subband1 = 301
subband2 = 302
cls = CorrelatedDataProduct
# Query for private data of the project, you must be member of the project
private_data = False

# All URIS to stage
uris = {
    project1: set(),
    project2: set(),
}

for project in (project1, project2) :
    print("Using project %s" % project)
    if private_data :
        context.set_project(project)
        if project != context.get_current_project().name:
            raise Exception("You are not member of project %s" % project)
    query_observations = Observation.select_all().project_only(project)
    for observation in query_observations :
        print("Querying ObservationID %s" % observation.observationId)
        dataproduct_query = cls.observations.contains(observation)
        # isValid = 1 means there should be an associated URI
        dataproduct_query &= cls.isValid == 1
        dataproduct_query &= ((cls.subband == subband1) | (cls.subband ==
subband2))
        # Or for stationSubband do :
        #dataproduct_query &= ((cls.stationSubband == subband1) |
(cls.stationSubband == subband2))
        for dataproduct in dataproduct_query :
            # This DataProduct should have an associated URL
            fileobject = ((FileObject.data_object == dataproduct) &
(FileObject.isValid > 0)).max('creation_date')
```

```

        if fileobject :
            print("URI found %s" % fileobject.URI)
            uris[project].add(fileobject.URI)
        else :
            print("No URI found for %s with dataProductIdentifier %d" %
                  (dataprodukt.__class__.__name__, dataprodukt.dataProductIdentifier))

for project in (project1, project2) :
    print("Total URI's found for project %s: %d" % (project,
len(uris[project])))

stager = LtaStager()
if do_stage :
    for project in (project1, project2) :
        stager.stage_uris(uris[project])

```

Here, we find data between freq1 and freq2 taken within one project between day1 and day2

```

do_stage = False
project = 'LC2_033'
freq1 = 172.0
freq2 = 178.0
day1 = datetime(2014,8,26) # this could include time; ie hours, minutes,
seconds
day2 = datetime(2014,8,29) # idem
# DataProduct class to query; CorrelatedDataProduct, SkyImageDataProduct,
etc ...
cls = CorrelatedDataProduct
# Query for private data of the project, you must be member of the project
private_data = False

# To see private data of this project, you must be member of this project
if private_data :
    context.set_project(project)
    if project != context.get_current_project().name:
        raise Exception("You are not member of project %s" % project)

query_observations = (
    (Observation.startTime >= day1) &
    (Observation.endTime < day2) ).project_only(project)

uris = set()
for observation in query_observations :
    print("Querying ObservationID %s" % observation.observationId)
    dataprodukt_query = cls.observations.contains(observation)
    # isValid = 1 means there should be an associated URI
    dataprodukt_query &= cls.isValid == 1
    dataprodukt_query &= cls.minimumFrequency >= freq1
    dataprodukt_query &= cls.maximumFrequency < freq2
    for dataprodukt in dataprodukt_query :
        # This DataProduct should have an associated URL

```

```

        fileobject = ((FileObject.data_object == dataproduct) &
(FileObject.isValid > 0)).max('creation_date')
        if fileobject :
            print("URI found %s" % fileobject.URI)
            uris.add(fileobject.URI)
        else :
            print("No URI found for %s with dataProductIdentifier %d" %
(dataproduct.__class__.__name__, dataproduct.dataProductIdentifier))

print("Total URI's found %d" % len(uris))

if do_stage :
    stager = LtaStager()
    stager.stage_uris(uris)

```

Example; query public data

Querying public data in projects you are not member of. First set project ALL, then construct a query and optionally limit the query to a certain project :

```

context.set_project('ALL')
query = CorrelatedDataProduct.select_all()
query &= query.project_only('LC0_017')
print(len(query))
# 1800

```

Python Module for Staging

The python interaction with the LTA catalog can be complemented with the use of a specific module developed to give users more control over their staging requests.

The module is made available [here](#) and its functions are self-explanatory.

For a description of what the user can do, we list here the functions that are available.

stage(surls)

It takes in a list of surls, queues a staging request for those urls, and outputs the ID of the request.

get_status(stageid)

It tells the user if a request is queued, in progress or finished (success).

abort(stageid)

It allows users to end a staging request.

get_surls_online(stageid)

It gives a list of the surls that have been staged for the relative request. The list is updated whenever a new surl comes on line.

get_srm_token(stageid)

The srm token is useful to interact directly with the SRM site through GRID/SRM tools.

reschedule(stageid)

If a request failed, it can be rescheduled.

get_progress()

No input needed. It returns the statuses of all the requests owned by the user.

Below is an example of how to use this:

```
> python
Python 2.7.10 (default, Oct 23 2015, 19:19:21)
[GCC 4.2.1 Compatible Apple LLVM 7.0.0 (clang-700.0.59.5)] on darwin
Type "help", "copyright", "credits" or "license" for more information.
>>> import stager_access as sa
2016-11-24 16:39:55.865000 stager_access: Parsing user credentials from
/Users/renting/.stagingrc
2016-11-24 16:39:55.865111 stager_access: Creating proxy
>>> sa.prettyprint(sa.get_progress())
+ 12227
- File count      ->      100
- Files done      ->       40
- Flagged abort    ->      false
- Location         ->      fz-juelich
- Percent done     ->       40
- Status          ->      on hold
- User id         ->      1919
```

From:

<https://www.astron.nl/lofarwiki/> - **LOFAR Wiki**

Permanent link:

https://www.astron.nl/lofarwiki/doku.php?id=public:lta_tricks&rev=1545134470

Last update: **2018-12-18 12:01**

