





Pointing Things at the Sky and some other things

09 March 2016

RRS and SALT




Tracker

Dome Drives &
Bogie
Assemblies

Structure Drive &
Control

SALT: Structure Drive and Pintle Bearing




- Air bearings for shock-free rotation
- Structure drives for azimuth rotation
- Pintle bearing assembly in the centre



SALT: Dome Rotation

- 12 Bogie Assemblies on top of ring wall I-beams
- 4 Dome drives rotate and control the dome to position the shutter



SALT: Tracker

- Total mass 4500 kg
- 13 m above mirror
- Positions payload in 2-D in a range of 3.25 m in each dimension
- Pointing accuracy of 6 microns in 10 axes of motion





CPV Plant at Touws River: 44 MW



CPV Plant at Touws River: Design

- Dual-axis tracker
- 105m² with 12 CPV panels
- Had to be designed, proto type erected and tested within 3 months
- Acceptance angle 0.1° up to 8m/s wind
- Drive working in elevation up to 22m/s
- Survive wind in stow up to 40m/s
- Wind force analysis
- FEA for structural deformation




CPV Plant at Touws River: Production

- Total mass of 1 tracker parts 2200kg
- Dual Axis Drive 600kg
- CPV Modules 12 x 240kg 2880kg
- Total 5680kg
- Total number of trackers 1540

- Do the math 3400 tons of steel

- All steel manufacturing done in Gauteng. Not enough capacity in Cape Town

CPV Plant at Touws River: Production




CPV Plant at Touws River: Lessons Learnt

- Murphy is alive!
- Contract negotiations are extremely tiring and frustrating for technical people
- Packaging for long distance transport is very important
- Make provision for 3 times your original QA budget
- This cannot be done without serious project management, config management and system engineering

RRS Systems Engineering and SKA1

- RRS has been involved with System Engineering on the SKA1 Project as a Member of the SKA1 CSP Consortium from the commencement of the Pre-Construction Phase in Nov 2013.
- RRS was responsible for the Integration and Verification Planning and assisted on Requirements Management for CSP.
- In June 2015 RRS, together with SKA SA, withdrew from the CSP Consortium and RRS started working with the SKA1 Dish Consortium.
- For Dish we are again involved in Integration and Verification Planning and Requirements Management

RRS Products




REUTECH
RADAR SYSTEMS

Receiver Characteristics

- **Pulse-Doppler**
 - Multiple down-conversion stages
 - Sample at IF
 - Typical bandwidth 5MHz to 40MHz
- **FMCW**
 - Single down-conversion
 - Sample at base band
 - Bandwidth ranges from 100kHz to 10MHz

“Low” Noise Receivers


- System Noise Figures vary from 2dB to 5dB
- Radars cannot be too sensitive because they observe the ground and sun, and they become more sensitive to Noise Jammers
- Receiver sub-systems contain Low Noise Components
 - L-Band LNA: 1dB NF
Developed at RRS



- X-Band LNA: Miteq 0.75dB NF



Receivers



- 950 MHz to 2150 MHz Direct down-conversion receiver
- 140 MHz instantaneous bandwidth
- Very high dynamic range
- Must be able to handle large CW input signals
- IQ unbalance (over frequency and temperature):
 - Magnitude: ≤ 0.3 dB peak, ≤ 0.1 dB Pk-Pk variation
 - Phase: ≤ 3 degrees peak, ≤ 0.5 degrees Pk-Pk variation

Summary

- We can do certain things
- We could do some of these things for AAMID



Contact Us

Tel: +27 21 880 1150
Fax: +27 21 880 1842

35 Electron Avenue
Technopark
Stellenbosch, 7600
South Africa

P.O. Box 686
Stellenbosch, 7599
South Africa